



# FUEL OX® HEATING OIL TREATMENT



Fuel Ox® Heating Oil Treatment has been specifically formulated to enhance the efficiency of indoor fuel systems and significantly decrease prevalent fuel-related problems and service calls during the winter season. It effectively addresses issues such as fuel stabilization, sludge buildup, water contamination, and corrosion.

In particular, bio-blend fuels tend to degrade at a faster rate and cause obstructions in the internal components of fuel systems. Additionally, fuel oxidation results in an acidic environment that leads to seal deterioration and interior component blockages. However, the Fuel Ox® Heating Oil Treatment prevents fuel oxidation and maintains the stability of bio-blends

## FEATURES

- 8oz treats 275 gallons
- Contains antioxidants to prevent acidity and breakdown of seals due to biofuels
- Removes water from the fuel (Emulsifier)
- Prevents and disperses formation of solids
- Lubricates the fuel system
- Cleans injectors
- Prevents internal tank corrosion
- Permits up to five year storage
- Reduces fuel-related service calls as a result of filter, strainer, and nozzles blockage

## STANDARDS

APPEARANCE:	Red liquid
ODOR:	Camphor Characteristic
FLASH POINT:	126°F
FORM:	Liquid
SOLUBILITY IN FUEL:	100%
FLAMMABILITY:	No data available
TREATMENT RATIO:	1 : 4,400

## RECOMMENDED USAGE

### WINTER USE

Before the onset of cold weather, pour one 8oz bottle of Fuel Ox® Heating Oil Treatment directly into fuel tank for every 275 gallons.

### SUMMER USE

To stabilize fuel for off season, double dose to ensure peak fuel system efficiency.

## TREATMENT RATIO

US SIZE	METRIC SIZE	GALLONS TREATED	LITERS TREATED
8 ounces	250 ml	275 gallons	1,040 L
55 gallon drum	208 liter drum	240,000 gallons	908,500 L