



INFINITY LUBE™ COOL-OX



Infinity Lube™ Cool-Ox reconditions, restores and maintains efficiency by improving heat transfer in condenser and evaporator coils in the air conditioning, heat pump and refrigeration systems. Cool-Ox is a metal conditioner and surface modifier that cleans and transitions metal surfaces into laminar surfaces with friction coefficients less than 0.1. This increase in lubricity makes A/C systems blow colder air and saves energy by having less run time. It is extremely important to note that Cool-Ox does not include elements of the halogen group such as chlorine, fluorine and sulfur that form highly corrosive acids like other competitors products. Cool-Ox does not contain PTFE (Teflon) or any other particulates like powdered metal or plastics. Cool-Ox has been thoroughly endorsed, tested and proven to be the only product of its kind. Whether you own a home or business this energy saving product is an absolute must and a tribute to American engineering.

FEATURES

- Plant based & toxin free
- Reduces electrical energy caused by friction of the contacting points
- Reduces up to 30% or more on electrical bill. Amperage reductions of up to 50%
- Improves pool boiling & thermodynamics which delivers colder vent air faster
- Reduces equipment maintenance costs & compressor noises
- Extends equipment/cooling systems life
- Reestablishes lost system SEER (seasonal energy efficient ratio) performance
- Reduces oil fouling
- Improves lubrication in compressor

APPLICATIONS

- HVAC/Air Conditioning (Residential & Commercial)
- Pre-Cooling & Manufacturing Processes
- Refrigeration storages, Transportation, & Distribution
- Automotive, Truck and Reefer A/C Systems

APPLICATION DIRECTIONS

One time treatment. Add one ounce to treat 1 ton of unit/rating.

SPECIFICATIONS

COLOR:	Tan to Brown
DENSITY:	7.8 lbs/gal (930 kg/m3)
FLASH POINT:	900°F (482°C)
SPECIFIC GRAVITY:	0.93
CHLORINE:	None
MINERAL OIL:	0%

AVAILABLE SIZES

3 oz
8 oz
64 oz
55 gallon drum