



# FUEL OX® FREEZE GUARD



Fuel Ox® Freeze Guard additive is a military grade anti-gel additive that prevents fuel systems from gelling and freezing and removing water. It is designed to reduce cold filter plugging point (CFPP) by as much as 45° (about 60° Pour Point).

## FEATURES

- 64oz of Fuel Ox® Freeze Guard treats up to 5,000 gallons of fuel
- Lowers CFPP and Pour Point
- Contains WASA- Wax Anti Settling Additives that prevent the crystals from clogging together and settle at the bottom of the fuel tank which then prevents fuel filters from clogging.
- Removes water

## SPECIFICATIONS

APPEARANCE:	Light amber liquid
ODOR:	Organic, Solvent
FLASH POINT:	100°F PMCC
FORM:	Liquid
SOLUBILITY IN FUEL:	100%
DENSITY:	7.57 lbs/gal
FLAMMABILITY:	Combustible liquid
TREATMENT RATIO:	1 : 10,000
CERTIFICATIONS:	ASTM (D-975)

## STANDARDS

- American Society for Testing and Materials Specification (ASTM-D975)
- Naval Sea Systems Command (SEA 51222)
- Military Specification (MIL-L87177a)
- Department of Defense Specification (DOD-A-24682)
- Environmental Protection Agency (EPA) Registered

## TREATMENT RATIO

US SIZE	METRIC SIZE	GALLONS TREATED	LITERS TREATED
64 ounces	1892 ml	5,000 gallons	18,927 L
1 gallon	3,785 ml	10,000 gallons	37,854 L
55 gallon drum	208 liter drum	550,000 gallons	2,080,000 L